

IN THE CLAIMS

Please amend the following claims which are pending in the present application:

1. (Currently Amended) A soft contact lens having a diameter of greater than the limbal diameter and formed of a homogenous material having an elastic modulus between 0.2 and 10 MPa, said lens having a generally concave posterior surface for fitting to the eye of a wearer, and a convex anterior surface, the contact lens having mechanical properties and/or a geometric shape such that when the lens is fitted to the eye the pressure applied to the eye by or via the lens will vary in a radial direction between at least one zone of higher pressure and at least one zone of lower pressure, the pressure gradient between said zones, and the location of said zones, being selected so as to cause a dimensional change to the surface layer of the cornea of the eye to thereby at least temporarily cause the refractive state of the eye to change.

2. (Original) A soft contact lens according to claim 1 wherein said posterior surface has a shape that differs from the contour of the eye such that a first annular portion of the lens at a selected radial distance from the center of the lens

will be closer to the surface of the eye than a second annular portion of the lens at a different second selected radial distance from the center of the lens.

3. (Original) A soft contact lens according to claim 2 wherein the pressures applied to the eye at the first annular portion and at the second annular portion are such as to define a pressure gradient which is sufficiently steep that epithelial thickness will tend to increase from the zone of high pressure towards the zone of low pressure.

4. (Currently Amended) A soft contact lens according to claim 1 wherein the lens is constructed so as to have a natural orientation and an everted orientation and is functional in both orientations, the lens being stable ~~in both~~ in the everted orientation ~~when placed on the eye~~, and wherein the posterior surface of the lens in said everted orientation is defined by the anterior surface of the lens in said natural orientation.

5. (Previously Presented) A soft contact lens according to claim 1 wherein the lens is formed of a material with oxygen transmissibility greater than 87 barrers.

6. (Cancelled)
7. (Previously Presented) A soft contact lens according to claim 1 wherein the lens is comprised of a silicone hydrogel material.
8. (Previously Presented) A soft contact lens according to claim 1 wherein the lens has a back vertex power of between +10D and -35D.
9. (Previously Presented) A soft contact lens according to claim 1 wherein the lens has a center thickness of between 0.04 mm and 0.31 mm.
10. (Previously Presented) A soft contact lens according to claim 1 having an annular zone of lower pressure at a distance less than approximately 4 mm from the center of the lens.
11. (Previously Presented) A soft contact lens according to claim 1 having an annular zone of higher pressure at a distance of approximately between 3 mm and 6 mm from the center of the lens.

12. (Previously Presented) A method of refractive error reduction of an eye by corneal reshaping including:

determining the required refractive correction for the eye;

characterizing the surface shape of at least that part of the eye which is to be subjected to reshaping; and

selecting a soft lens formed of a material and having a geometric configuration such that when fitted to the eye will apply pressures to the surface of the eye in such manner as to assist in the required corneal reshaping.

13. (Original) A method according to claim 12 wherein said selection process involves a modeling process adapted to predict anticipated pressures and different zones of the wearer's eye.

14. (Original) A method according to claim 13 wherein said modeling process is a finite element modeling process.

15. (New) A method according to claim 12 wherein the lens selected is of a type that has been manufactured so as to have a natural orientation and an everted orientation and is functional in both orientations, said lens being stable in the everted orientation when placed on the eye.